ZORON W4R

Round Wall Mount





Fixture Type:	
Catalog Number:	
Project:	
Location:	

PRODUCT DESCRIPTION

The Zoron series combines sleek aesthetics with exceptional performance. Compact and stylish enough for residential applications, yet powerful enough to be used commercially. With built-in color temperature selection and the option to be used either indoors or out, Zoron adapts to any setting. Regressed trims and specialized TIR optics provide both aesthetic appeal and glare control, making Zoron the perfect blend of form and function.

FEATURES

- · Die-cast aluminum construction
- 5-CCT Switchable between 2700K and 5000K
- · Suitable for indoor or outdoor use
- Low glare regressed trim with 25°+ shielding angle
- · Driver concealed within the fixture

SPECIFICATIONS

Input: Universal voltage 120V - 277VAC, 50/60Hz

Dimming: ELV, TRIAC, 0-10V: 100-5%

Light Source: Integrated LED

Finish: Electrostatically powder coated: White, Black

Injection molded polycarbonate: Black, Chrome, Gold,

Ø3%" —

Haze, White


Standards: UL, cUL, IP65, Title 24 JA8 Compliant, Wet Location


Listed

41/2" —

Operating Temp: -13°F to 122°F (-25°C to 50°C)

LINE DRAWING





Standard Trim Arc Trim

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 **Headquarters, East Manufacturing Facility**44 Harbor Park Drive
Port Washington, NY 11050

South East Manufacturing Facility 1600 Distribution Ct Lithia Springs, GA 30122 **Central Manufacturing Facility** 1700 South J Elmer Freeway, Ste 100 Cedar Hill, TX 75104 **West Manufacturing Facility** 1750 S Archibald Ave Ontario, CA 91761

1

ZORON W4R

Round Wall Mount



Standard Trim

Model	Power	. Beam		Color Temp		CRI	Lumens	СВСР	Efficacy (lm/W)	Body Finish	Trim Finish
W4R 15W	15\W	N Narrow	25°	CS	2700K 3000K 3500K 4000K 5000K	90	1015 1060 1100 1130 1185	2985 3310 3235 3330 3485	68 71 73 75 79	BK Black WT White	BK Black CH Chrome GL Gold HZ Haze WT White
	1300	F Flood	45°	cs	2700K 3000K 3500K 4000K 5000K	90	1135 1180 1230 1265 1325	1945 2025 2105 2165 2265	76 79 82 84 88	BK Black WT White	BK Black CH Chrome GL Gold HZ Haze WT White

W4R-_CS-_

Example: W4R-FCS-WTHZ

Arc Trim

Model	Power	Beam	Beam Color T		Temp	CRI	Lumens	СВСР	Efficacy (lm/W)	Trim Finish	1 *
W4R 15W	N Narrow	25°	cs	2700K 3000K 3500K 4000K 5000K	90	910 945 985 1010 1060	3075 3200 3330 3425 3585	61 63 66 67 71	PBK PWT	Arc Black Arc White	
	F Flood	45°	cs	2700K 3000K 3500K 4000K 5000K	90	1065 1110 1150 1185 1240	1950 2035 2115 2175 2275	71 74 77 79 83	PBK PWT	Arc Black Arc White	

W4R-_CS-P__ Example: W4R-NCS-PBK *When ordering Arc trim, body finish will match trim finish.